


บริษัท เพรสแมน (ประเทศไทย) จำกัด
Presmann (Thailand) Co., Ltd.

Presmann Ice Bank Beer Cooler



High performance agitator which is easily serviced or replaced without disconnecting beer lines.

Thermostat and all components accessible from outside the water bath. No need to ever remove chiller lid or disconnect beer lines for field service.

Many connection options available

Beer and coolant lines are grouped for easy installation and maximum cooling effect.

High performance refrigeration package is tuned for tropical climates so your beer is always cold.

Tough, corrosion proof insulated unibody construction. Fewer parts. Longer service.



Castors included.

Specifications

Model	U14
Dimensions	450 x 450 x 860 mm
Empty Weight	40 kg
Operational Weight	68 kg
Ice bank capacity	14 kg
Refrigerant	R134a
Ice bank control	Mechanical pre-set
Beer coil (1-4 coils)	AISI-316 6 or 8 mm
Compressor	3/8 hp
Cooling capacity @ -10 SST	720 watts
Pull down time @ 30C ambient and water bath	3 hrs, 40 minutes
Agitator / pump motor (MID-8)	55 watts
Condensor fan motor	25 watts
Voltage	220-230V / 50 HZ / 1 PH
Run current	3.5 amps
Castors included	2" rubber